


AD-A189 796


ADA (TRADE NAME) COMPILER VALIDATION SUMMARY REPORT  
TELESOFT PRIME ADA C (U) INFORMATION SYSTEMS AND  
TECHNOLOGY CENTER W-P AFB OH ADA VALI 21 APR 87  
AVF-VSR-73 8687 F/G 12/5

1/1

UNCLASSIFIED

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A189 796

PAGE

1. REF	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Ada Compiler Validation Summary Report: TeleSoft. Prime Ada Compiler, Version 1.0. Prime 9955 Model 2	5. TYPE OF REPORT & PERIOD COVERED 21 Apr 1987 to 21 Apr 1988	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Wright-Patterson AFB	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION AND ADDRESS Ada Validation Facility ASD/SIOL Wright-Patterson AFB OH 45433-6503	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
11. CONTROLLING OFFICE NAME AND ADDRESS Ada Joint Program Office United States Department of Defense Washington, DC 20301-3081	12. REPORT DATE 21 April 1987	13. NUMBER OF PAGES 34
14. MONITORING AGENCY NAME & ADDRESS (If different from Controlling Office) Wright-Patterson	15. SECURITY CLASS (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20. If different from Report)  UNCLASSIFIED		
18. SUPPLEMENTARY NOTES		
19. KEYWORDS (Continue on reverse side if necessary and identify by block number)  Ada Programming language, Ada Compiler Validation Summary Report, Ada Compiler Validation Capability, ACVC, Validation Testing, Ada Validation Office, AVO, Ada Validation Facility, AVF, ANSI/MIL-STD- 1815A, Ada Joint Program Office, AJPO		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  See Attached		

DTIC  
ELECTE  
JAN 06 1988  
S D

DD FORM

1473

EDITION OF 1 NOV 65 IS OBSOLETE

1 JAN 73

S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

## INTRODUCTION

### 1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT

This VSR documents the results of the validation testing performed on an Ada compiler. Testing was carried out for the following purposes:

- . To attempt to identify any language constructs supported by the compiler that do not conform to the Ada Standard
- . To attempt to identify any unsupported language constructs required by the Ada Standard
- . To determine that the implementation-dependent behavior is allowed by the Ada Standard

Testing of this compiler was conducted by SofTech, Inc., under the direction of the AVF according to policies and procedures established by the Ada Validation Organization (AVO). On-site testing was conducted from 20 April 1987 through 21 April 1987 at TeleSoft in San Diego CA.

### 1.2 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the AVO may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject compiler has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from:

Ada Information Clearinghouse  
Ada Joint Program Office  
OUSDRE  
The Pentagon, Rm 3D-139 (Fern Street)  
Washington DC 20301-3081

or from:

Ada Validation Facility  
ASD/SCOL  
Wright-Patterson AFB OH 45433-6503

## EXECUTIVE SUMMARY

This Validation Summary Report (VSR) summarizes the results and conclusions of validation testing performed on the Prime Ada Compiler, Version 1.0, using Version 1.8 of the Ada<sup>®</sup> Compiler Validation Capability (ACVC). The Prime Ada Compiler is hosted on a Prime 9955 Model 2 operating under Primos, Revision 20.0.7.R1. Programs processed by this compiler may be executed on a Prime 9955 Model 2 operating under Primos, Revision 20.0.7.R1.

On-site testing was performed 20 April 1987 through 21 April 1987 at TeleSoft in San Diego CA, under the direction of the Ada Validation Facility (AVF), according to Ada Validation Organization (AVO) policies and procedures. The AVF identified 2138 of the 2399 tests in ACVC Version 1.8 to be processed during on-site testing of the compiler. The 19 tests withdrawn at the time of validation testing, as well as the 242 executable tests that make use of floating-point precision exceeding that supported by the implementation, were not processed. After the 2138 tests were processed, results for Class A, C, D, and E tests were examined for correct execution. Compilation listings for Class B tests were analyzed for correct diagnosis of syntax and semantic errors. Compilation and link results of Class L tests were analyzed for correct detection of errors. There were 52 of the processed tests determined to be inapplicable. The remaining 2086 tests were passed.

The results of validation are summarized in the following table:

RESULT	CHAPTER													TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14		
Passed	96	222	298	242	161	97	136	262	107	32	217	216	2086	
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0	
Inapplicable	20	103	122	5	0	0	3	0	23	0	1	17	294	
Withdrawn	0	5	5	0	0	1	1	2	4	0	1	0	19	
TOTAL	116	330	425	247	161	98	140	264	134	32	219	233	2399	

The AVF concludes that these results demonstrate acceptable conformity to ANSI/MIL-STD-1815A Ada.

---

<sup>®</sup>Ada is a registered trademark of the United States Government (Ada Joint Program Office).

AVF Control Number: AVF-VSR-73.0687  
87-01-29-TEL

Ada® COMPILER  
VALIDATION SUMMARY REPORT:  
TeleSoft  
Prime Ada Compiler, Version 1.0  
Prime 9955 Model 2

Completion of On-Site Testing:  
21 April 1987

Prepared By:  
Ada Validation Facility  
ASD/SCOL  
Wright-Patterson AFB OH 45433-6503

Prepared For:  
Ada Joint Program Office  
United States Department of Defense  
Washington, D.C.

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

---

®Ada is a registered trademark of the United States Government  
(Ada Joint Program Office).

+++++  
+ +  
+ Place NTIS form here +  
+ +  
+++++

Ada<sup>®</sup> Compiler Validation Summary Report:

Compiler Name: Prime Ada Compiler, Version 1.0

Host:


Prime 9955 Model 2  
under Primos, Revision 20.0.7.R1

Target:

Prime 9955 Model 2  
under Primos, Revision 20.0.7.R1

Testing Completed 21 April 1987 Using ACVC 1.8

This report has been reviewed and is approved.



Ada Validation Facility  
Georgeanne Chitwood  
ASD/SCOL  
Wright-Patterson AFB OH 45433-6503



Ada Validation Organization  
Dr. John F. Kramer  
Institute for Defense Analyses  
Alexandria VA



Ada Joint Program Office  
Virginia L. Castor  
Director  
Department of Defense  
Washington DC

<sup>®</sup>Ada is a registered trademark of the United States Government  
(Ada Joint Program Office).



## EXECUTIVE SUMMARY

This Validation Summary Report (VSR) summarizes the results and conclusions of validation testing performed on the Prime Ada Compiler, Version 1.0, using Version 1.8 of the Ada<sup>®</sup> Compiler Validation Capability (ACVC). The Prime Ada Compiler is hosted on a Prime 9955 Model 2 operating under Primos, Revision 20.0.7.R1. Programs processed by this compiler may be executed on a Prime 9955 Model 2 operating under Primos, Revision 20.0.7.R1.

On-site testing was performed 20 April 1987 through 21 April 1987 at TeleSoft in San Diego CA, under the direction of the Ada Validation Facility (AVF), according to Ada Validation Organization (AVO) policies and procedures. The AVF identified 2138 of the 2399 tests in ACVC Version 1.8 to be processed during on-site testing of the compiler. The 19 tests withdrawn at the time of validation testing, as well as the 242 executable tests that make use of floating-point precision exceeding that supported by the implementation, were not processed. After the 2138 tests were processed, results for Class A, C, D, and E tests were examined for correct execution. Compilation listings for Class B tests were analyzed for correct diagnosis of syntax and semantic errors. Compilation and link results of Class L tests were analyzed for correct detection of errors. There were 52 of the processed tests determined to be inapplicable. The remaining 2086 tests were passed.

The results of validation are summarized in the following table:

RESULT	CHAPTER													TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14		
Passed	96	222	298	242	161	97	136	262	107	32	217	216	2086	
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0	
Inapplicable	20	103	122	5	0	0	3	0	23	0	1	17	294	
Withdrawn	0	5	5	0	0	1	1	2	4	0	1	0	19	
TOTAL	116	330	425	247	161	98	140	264	134	32	219	233	2399	

The AVF concludes that these results demonstrate acceptable conformity to ANSI/MIL-STD-1815A Ada.

---

<sup>®</sup>Ada is a registered trademark of the United States Government  
(Ada Joint Program Office).

## TABLE OF CONTENTS

CHAPTER 1	INTRODUCTION	
1.1	PURPOSE OF THIS VALIDATION SUMMARY REPORT . . . . .	1-2
1.2	USE OF THIS VALIDATION SUMMARY REPORT . . . . .	1-2
1.3	REFERENCES . . . . .	1-3
1.4	DEFINITION OF TERMS . . . . .	1-3
1.5	ACVC TEST CLASSES . . . . .	1-4
CHAPTER 2	CONFIGURATION INFORMATION	
2.1	CONFIGURATION TESTED . . . . .	2-1
2.2	IMPLEMENTATION CHARACTERISTICS . . . . .	2-1
CHAPTER 3	TEST INFORMATION	
3.1	TEST RESULTS . . . . .	3-1
3.2	SUMMARY OF TEST RESULTS BY CLASS . . . . .	3-1
3.3	SUMMARY OF TEST RESULTS BY CHAPTER . . . . .	3-2
3.4	WITHDRAWN TESTS . . . . .	3-2
3.5	INAPPLICABLE TESTS . . . . .	3-2
3.6	SPLIT TESTS . . . . .	3-4
3.7	ADDITIONAL TESTING INFORMATION . . . . .	3-4
3.7.1	Prevalidation . . . . .	3-4
3.7.2	Test Method . . . . .	3-4
3.7.3	Test Site . . . . .	3-5
APPENDIX A	DECLARATION OF CONFORMANCE	
APPENDIX B	APPENDIX F OF THE Ada STANDARD	
APPENDIX C	TEST PARAMETERS	
APPENDIX D	WITHDRAWN TESTS	

## CHAPTER 1

### INTRODUCTION

This Validation Summary Report (VSR) describes the extent to which a specific Ada compiler conforms to the Ada Standard, ANSI/MIL-STD-1815A. This report explains all technical terms used within it and thoroughly reports the results of testing this compiler using the Ada Compiler Validation Capability (ACVC). An Ada compiler must be implemented according to the Ada Standard, and any implementation-dependent features must conform to the requirements of the Ada Standard. The Ada Standard must be implemented in its entirety, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Ada Standard, it must be understood that some differences do exist between implementations. The Ada Standard permits some implementation dependencies--for example, the maximum length of identifiers or the maximum values of integer types. Other differences between compilers result from characteristics of particular operating systems, hardware, or implementation strategies. All of the dependencies observed during the process of testing this compiler are given in this report.

The information in this report is derived from the test results produced during validation testing. The validation process includes submitting a suite of standardized tests, the ACVC, as inputs to an Ada compiler and evaluating the results. The purpose of validating is to ensure conformity of the compiler to the Ada Standard by testing that the compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent but permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, and during execution.

Questions regarding this report or the validation test results should be directed to the AVF listed above or to:

Ada Validation Organization  
Institute for Defense Analyses  
1801 North Beauregard Street  
Alexandria VA 22311

### 1.3 REFERENCES

1. Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983.
2. Ada Validation Organization: Policies and Procedures, Ada Joint Program Office, 1 January 1987.
3. Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., December 1984.

### 1.4 DEFINITION OF TERMS

ACVC	The Ada Compiler Validation Capability. A set of programs that evaluates the conformity of a compiler to the Ada language specification, ANSI/MIL-STD-1815A.
Ada Standard	ANSI/MIL-STD-1815A, February 1983.
Applicant	The agency requesting validation.
AVF	The Ada Validation Facility. In the context of this report, the AVF is responsible for conducting compiler validations according to established policies and procedures.
AVO	The Ada Validation Organization. In the context of this report, the AVO is responsible for setting procedures for compiler validations.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	A test for which the compiler generates a result that demonstrates nonconformity to the Ada Standard.
Host	The computer on which the compiler resides.

## INTRODUCTION

Inapplicable test	A test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.
Passed test	A test for which a compiler generates the expected result.
Target	The computer for which a compiler generates code.
Test	A program that checks a compiler's conformity regarding a particular feature or features to the Ada Standard. In the context of this report, the term is used to designate a single test, which may comprise one or more files.
Withdrawn test	A test found to be incorrect and not used to check conformity to the Ada language specification. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains illegal or erroneous use of the language.

### 1.5 ACVC TEST CLASSES

Conformity to the Ada Standard is measured using the ACVC. The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable, and special program units are used to report their results during execution. Class B tests are expected to produce compilation errors. Class L tests are expected to produce link errors.

Class A tests check that legal Ada programs can be successfully compiled and executed. However, no checks are performed during execution to see if the test objective has been met. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a PASSED message.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that every syntax or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler.

Class C tests check that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASSED, FAILED, or NOT APPLICABLE message indicating the result when it is executed.

Class D tests check the compilation and execution capacities of a compiler. Since there are no capacity requirements placed on a compiler by the Ada Standard for some parameters--for example, the number of identifiers

permitted in a compilation or the number of units in a library--a compiler may refuse to compile a Class D test and still be a conforming compiler. Therefore, if a Class D test fails to compile because the capacity of the compiler is exceeded, the test is classified as inapplicable. If a Class D test compiles successfully, it is self-checking and produces a PASSED or FAILED message during execution.

Each Class E test is self-checking and produces a NOT APPLICABLE, PASSED, or FAILED message when it is compiled and executed. However, the Ada Standard permits an implementation to reject programs containing some features addressed by Class E tests during compilation. Therefore, a Class E test is passed by a compiler if it is compiled successfully and executes to produce a PASSED message, or if it is rejected by the compiler for an allowable reason.

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time--that is, an attempt to execute the main program must generate an error message before any declarations in the main program or any units referenced by the main program are elaborated.

Two library units, the package REPORT and the procedure CHECK\_FILE, support the self-checking features of the executable tests. The package REPORT provides the mechanism by which executable tests report PASSED, FAILED, or NOT APPLICABLE results. It also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The procedure CHECK\_FILE is used to check the contents of text files written by some of the Class C tests for chapter 14 of the Ada Standard. The operation of these units is checked by a set of executable tests. These tests produce messages that are examined to verify that the units are operating correctly. If these units are not operating correctly, then the validation is not attempted.

The text of the tests in the ACVC follow conventions that are intended to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic set of 55 characters, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be supported by all implementations in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values--for example, an illegal file name. A list of the values used for this validation is provided in Appendix C.

A compiler must correctly process each of the tests in the suite and demonstrate conformity to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. The applicability of a test to an implementation is considered each time the implementation is validated. A test that is inapplicable for one validation is not necessarily inapplicable for a subsequent validation.

## INTRODUCTION

Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC and, therefore, is not used in testing a compiler. The tests withdrawn at the time of validation are given in Appendix D.

## CHAPTER 2

### CONFIGURATION INFORMATION

#### 2.1 CONFIGURATION TESTED

The candidate compilation system for this validation was tested under the following configuration:

Compiler: Prime Ada Compiler, Version 1.0

ACVC Version: 1.8

Certificate Number: 870420W1.08049

Host Computer:

Machine:	Prime 9955 Model 2
Operating System:	Primos, Revision 20.0.7.R1
Memory Size:	32 megabytes

Target Computer:

Machine:	Prime 9955 Model 2
Operating System:	Primos, Revision 20.0.7.R1
Memory Size:	32 megabytes

#### 2.2 IMPLEMENTATION CHARACTERISTICS

One of the purposes of validating compilers is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, tests in other classes also characterize an implementation. This compiler is characterized by the following



## CONFIGURATION INFORMATION

interpretations of the Ada Standard:

- . Capacities.

The compiler correctly processes tests containing loop statements nested to 65 levels, block statements nested to 65 levels, and recursive procedures separately compiled as subunits nested to 17 levels. It correctly processes a compilation containing 723 variables in the same declarative part. (See tests D55A03A..H (8 tests), D56001B, D64005E..G (3 tests), and D29002K.)

- . Universal integer calculations.

An implementation is allowed to reject universal integer calculations having values that exceed `SYSTEM.MAX_INT`. This implementation does not reject such calculations and processes them correctly. (See tests D4A002A, D4A002B, D4A004A, and D4A004B.)

- . Predefined types.

This implementation supports the additional predefined types `LONG_INTEGER` and `LONG_FLOAT` in the package `STANDARD`. (See tests B86001C and B86001D.)

- . Based literals.

An implementation is allowed to reject a based literal with a value exceeding `SYSTEM.MAX_INT` during compilation, or it may raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` during execution. This implementation raises `NUMERIC_ERROR` during execution. (See test E24101A.)

- . Array types.

An implementation is allowed to raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` for an array having a `'LENGTH` that exceeds `STANDARD.INTEGER'LAST` and/or `SYSTEM.MAX_INT`.

A packed `BOOLEAN` array having a `'LENGTH` exceeding `INTEGER'LAST` raises `NUMERIC_ERROR` when the array type is declared. (See test C52103X.)

A packed two-dimensional `BOOLEAN` array with more than `INTEGER'LAST` components raises `NUMERIC_ERROR` when the array type is declared. (See test C52104Y.)

A null array with one dimension of length greater than INTEGER'LAST may raise NUMERIC\_ERROR or CONSTRAINT\_ERROR either when declared or assigned. Alternatively, an implementation may accept the declaration. However, lengths must match in array slice assignments. This implementation raises NUMERIC\_ERROR when the array type is declared. (See test E52103Y.)

In assigning one-dimensional array types, the expression appears to be evaluated in its entirety before CONSTRAINT\_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. In assigning two-dimensional array types, the expression does not appear to be evaluated in its entirety before CONSTRAINT\_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- . Discriminated types.

During compilation, an implementation is allowed to either accept or reject an incomplete type with discriminants that is used in an access type definition with a compatible discriminant constraint. This implementation accepts such subtype indications during compilation. (See test E38104A.)

In assigning record types with discriminants, the expression appears to be evaluated in its entirety before CONSTRAINT\_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- . Aggregates.

In the evaluation of a multi-dimensional aggregate, the order in which choices are evaluated and index subtype checks are made appears to depend upon the aggregate itself. (See tests C43207A and C43207B.)

In the evaluation of an aggregate containing subaggregates, all choices are not evaluated before being checked for identical bounds. (See test E43212B.)

All choices are evaluated before CONSTRAINT\_ERROR is raised if a bound in a nonnull range of a nonnull aggregate does not belong to an index subtype. (See test E43211B.)

- . Functions.

An implementation may allow the declaration of a parameterless function and an enumeration literal having the same profile in the same immediate scope, or it may reject the function declaration. If it accepts the function declaration, the use of the enumeration

## CONFIGURATION INFORMATION

literal's identifier denotes the function. This implementation rejects the declaration. (See test E66001D.)

- Representation clauses.

The Ada Standard does not require an implementation to support representation clauses. If a representation clause is not supported, then the implementation must reject it. While the operation of representation clauses is not checked by Version 1.8 of the ACVC, they are used in testing other language features. This implementation accepts 'SIZE and 'STORAGE\_SIZE for tasks; it rejects 'STORAGE\_SIZE for collections and 'SMALL clauses. Enumeration representation clauses, including those that specify noncontiguous values, appear not to be supported. (See tests C55B16A, C87B62A, C87B62B, C87B62C, and BC1002A.)

- Pragmas.

The pragma INLINE is not supported for procedures or functions. (See tests CA3004E and CA3004F.)

- Input/output.

The package SEQUENTIAL\_IO cannot be instantiated with unconstrained array types and record types with discriminants. The package DIRECT\_IO cannot be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101C, AE2101H, CE2201D, CE2201E, and CE2401D.)

An existing text file can be opened in OUT\_FILE mode, can be created in OUT\_FILE mode, and cannot be created in IN\_FILE mode. (See test EE3102C.)

More than one internal file can be associated with each external file for text I/O for reading only. (See tests CE3111A..E (5 tests).)

More than one internal file can be associated with each external file for sequential I/O for reading only. (See tests CE2107A..F (6 tests).)

More than one internal file can be associated with each external file for direct I/O for reading only. (See tests CE2107A..F (6 tests).)

Temporary sequential files are given a name. Temporary direct files are given a name. Temporary files given names are deleted when they are closed. (See tests CE2108A and CE2108C.)

. Generics.

Generic subprogram declarations and bodies cannot be compiled in separate compilations. (See test CA2009F.)

Generic package declarations and bodies cannot be compiled in separate compilations. (See tests CA2009C and BC3205D.)

## CHAPTER 3

### TEST INFORMATION

#### 3.1 TEST RESULTS

Version 1.8 of the ACVC contains 2399 tests. When validation testing of Prime Ada Compiler was performed, 19 tests had been withdrawn. The remaining 2380 tests were potentially applicable to this validation. The AVF determined that 294 tests were inapplicable to this implementation, and that the 2086 applicable tests were passed by the implementation.

The AVF concludes that the testing results demonstrate acceptable conformity to the Ada Standard.

#### 3.2 SUMMARY OF TEST RESULTS BY CLASS

RESULT	TEST CLASS						TOTAL
	A	B	C	D	E	L	
Passed	67	862	1098	17	11	31	2086
Failed	0	0	0	0	0	0	0
Inapplicable	2	5	270	0	2	15	294
Withdrawn	0	7	12	0	0	0	19
TOTAL	69	874	1380	17	13	46	2399

## TEST INFORMATION

### 3.3 SUMMARY OF TEST RESULTS BY CHAPTER

RESULT	CHAPTER														TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14			
Passed	96	222	298	242	161	97	136	262	107	32	217	216			2086
Failed	0	0	0	0	0	0	0	0	0	0	0	0			0
Inapplicable	20	103	122	5	0	0	3	0	23	0	1	17			294
Withdrawn	0	5	5	0	0	1	1	2	4	0	1	0			19
TOTAL	116	330	425	247	161	98	140	264	134	32	219	233			2399

### 3.4 WITHDRAWN TESTS

The following 19 tests were withdrawn from ACVC Version 1.8 at the time of this validation:

C32114A	B37401A	B49006A	C92005A
B33203C	C41404A	B4A010C	C940ACA
C34018A	B45116A	B74101B	CA3005A..D (4 tests)
C35904A	C48008A	C87B50A	BC3204C

See Appendix D for the reason that each of these tests was withdrawn.

### 3.5 INAPPLICABLE TESTS

Some tests do not apply to all compilers because they make use of features that a compiler is not required by the Ada Standard to support. Others may depend on the result of another test that is either inapplicable or withdrawn. The applicability of a test to an implementation is considered each time a validation is attempted. A test that is inapplicable for one validation is not necessarily inapplicable for a subsequent attempt. For this validation attempt, 294 tests were inapplicable for the reasons indicated:

- C34001D, B52004E, B55B09D, and C55B07B use SHORT\_INTEGER which is not supported by this compiler.
- C34001F and C35702A use SHORT\_FLOAT which is not supported by this compiler.
- C52008B declares a record type with four discriminants of type integer and having default values. The type may be used in the declaration of unconstrained objects, but the size of these

objects exceeds the maximum object size of this implementation, and `NUMERIC_ERROR` is raised.

- . C55B16A makes use of an enumeration representation clause containing noncontiguous values which is not supported by this compiler.
- . B86001D requires a predefined numeric type other than those defined by the Ada language in package `STANDARD`. There is no such type for this implementation.
- . C86001F redefines package `SYSTEM`, but `TEXT_IO` is made obsolete by this new definition in this implementation and the test cannot be executed since the package `REPORT` is dependent on the package `TEXT_IO`.
- . C87B62B uses the length clause '`STORAGE_SIZE`' for access types which is not supported by this compiler. The length clause is rejected at compile time.
- . BA1011C, CA1012A, CA2009C, CA2009F, LA5008A..H (8 tests), LA5008J, LA5008M, LA5008N, and BC3205D compile generic specifications and bodies in separate compilations which is not supported by this compiler.
- . CA3004E, EA3004C, and LA3004A use `INLINE` pragma for procedures which is not supported by this compiler.
- . CA3004F, EA3004D, and LA3004B use `INLINE` pragma for functions which is not supported by this compiler.
- . LA5008I and LA5008K are inapplicable because, in this implementation, a generic unit is made obsolete by the recompilation of a unit on which the generic body (but not the specification) depends. Since this implementation does not support separate compilation of generic unit specifications and bodies, a generic specification must be considered obsolete whenever the body is found to be obsolete. These tests should report at link time that the body of a generic unit is obsolete. However, a compile-time error message reports that the generic unit is obsolete.
- . AE2101C, CE2201D, and CE2201E use an instantiation of package `SEQUENTIAL_IO` with unconstrained array types which is not supported by this compiler.
- . AE2101H and CE2401D use an instantiation of package `DIRECT_IO` with unconstrained array types which is not supported by this compiler.
- . CE2107B..E (4 tests), CE2110B, CE2111D, CE2111H, CE3111B..E (4 tests), and CE3114B are inapplicable because multiple internal files cannot be associated with the same external file except when the internal files are open for reading. The proper exception is

## TEST INFORMATION

raised when multiple access is attempted.

- . The following 242 tests require a floating-point accuracy that exceeds the maximum of 15 supported by the implementation:

C24113F..Y (20 tests)	C35708F..Y (20 tests)	C45421F..Y (20 tests)
C35705F..Y (20 tests)	C35802F..Y (20 tests)	C45424F..Y (20 tests)
C35706F..Y (20 tests)	C45241F..Y (20 tests)	C45521F..Z (21 tests)
C35707F..Y (20 tests)	C45321F..Y (20 tests)	C45621F..Z (21 tests)

### 3.6 SPLIT TESTS

If one or more errors do not appear to have been detected in a Class B test because of compiler error recovery, then the test is split into a set of smaller tests that contain the undetected errors. These splits are then compiled and examined. The splitting process continues until all errors are detected by the compiler or until there is exactly one error per split. Any Class A, Class C, or Class E test that cannot be compiled and executed because of its size is split into a set of smaller subtests that can be processed.

Splits were required for 8 Class B tests.

B26005A	BA3006B	BA3008B
BA1101C	BA3007B	BA3013A
BA3006A	BA3008A	

### 3.7 ADDITIONAL TESTING INFORMATION

#### 3.7.1 Prevalidation

Prior to validation, a set of test results for ACVC Version 1.8 produced by the Prime Ada Compiler was submitted to the AVF by the applicant for review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests, and that the compiler exhibited the expected behavior on all inapplicable tests.

#### 3.7.2 Test Method

Testing of the Prime Ada Compiler using ACVC Version 1.8 was conducted on-site by a validation team from the AVF. The configuration consisted of a Prime 9955 Model 2 host operating under Primos, Revision 20.0.7.R1, and a Prime 9955 Model 2 target operating under Primos, Revision 20.0.7.R1.



A magnetic tape containing all tests except withdrawn tests and tests requiring unsupported floating-point precisions was taken on-site by the validation team for processing. Tests that make use of implementation-specific values were customized before being written to the magnetic tape. Tests requiring splits during the prevalidation testing were included in their split form on the magnetic tape.

The contents of the magnetic tape were loaded directly onto the host computer. After the test files were loaded to disk, the full set of tests was compiled on the Prime 9955 Model 2, and all executable tests were linked and run. Tests were run in groups of approximately seventy tests according to class within chapter. Compilation listings for the Class B tests were printed as were the output from the linker for the Class L tests and the results for all other tests. Job logs were also printed.

The compiler was tested using command scripts provided by TeleSoft and reviewed by the validation team. The following options were explicitly in effect for testing:

<u>Option</u>	<u>Effect</u>
-NQ	No query when an error is deleted.
-LIST	Produce a listing (Class B, Class E, Class L, and inapplicable tests only).
-M	Monitor progress of the compilation.

Tests were compiled, linked, and executed (as appropriate) using three batch queues on a computer. Test output, compilation listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

### 3.7.3 Test Site

The validation team arrived at TeleSoft in San Diego CA on 20 April 1987, and departed after testing was completed on 21 April 1987.

APPENDIX A

DECLARATION OF CONFORMANCE

TeleSoft has submitted the following declaration of conformance concerning the Prime Ada Compiler.

## DECLARATION OF CONFORMANCE


Compiler Implementor: TeleSoft, Inc.  
Ada Validation Facility: ASD/SIOL, Wright-Patterson AFB, OH  
Ada Compiler Validation Capability (ACVC), Version 1.8

### Base Configuration

Base Compiler Name: Prime Ada Compiler, Version 1.0  
Host Architecture ISA: Prime 9955 Model 2  
Operating System: Primos Rev. 20.0.7.R1  
Target Architecture ISA: Prime 9955 Model 2  
Operating System: Primos Rev. 20.0.7.R1

### Implementor's Declaration

I, the undersigned, representing TeleSoft have implemented no deliberate extensions to the Ada Language Standard ANSI/MIL-STD-1815A in the compiler listed in this declaration. I declare that Prime Computer, Inc. is TeleSoft's exclusive licensee of the Ada language compiler listed above and, as such, is responsible for maintaining said compiler in conformance to ANSI/MIL-STD-1815A. All certificates and registrations for Ada language compiler listed in this declaration shall be made only in the exclusive licensee's corporate name.

  
\_\_\_\_\_  
TeleSoft, Inc.

Date: 4/21/87

Raymond A. Parra, Director, Contracts & Legal

### Licensee's Declaration

I, the undersigned, representing Prime Computer, Inc. take full responsibility for implementation and maintenance of the Ada compiler listed above, and agree to the public disclosure of the final Validation Summary Report. I further agree to continue to comply with the Ada trademark policy, as defined by the Ada Joint Program Office. I declare that all of the Ada language compilers listed, and their host/target performance are in compliance with the Ada Language Standard ANSI/MIL-STD-1815A. I have reviewed the Validation Summary Report for the compiler listed and concur with the contents.

  
\_\_\_\_\_  
Prime Computer, Inc.  
Stan Zaborowski, Ada Project Leader

Date: 4/21/87

"Ada" is a registered trademark of the U.S. Government, Ada Joint Program Office.

## APPENDIX B

### APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in chapter 13 of MIL-STD-1815A, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of the Prime Ada Compiler, Version 1.0, are described in the following sections which discuss topics in Appendix F of the Ada Language Reference Manual (ANSI/MIL-STD-1815A).

Implementation-specific portions of the package STANDARD are:

```
package STANDARD is
```

```
...
```

```
type INTEGER is range -32_768 .. 32_767;
```

```
type LONG_INTEGER is range -2_147_483_648 .. 2_147_483_647;
```

```
type FLOAT is digits 6 range -1.70141E+38 .. 1.70141E+38;
```

```
type LONG_FLOAT is digits 9 range -1.70141183E+38 .. 1.70141183E+38;
```

```
type DURATION is delta 2#1.0#e-14 range -86_400.0 .. 86_400.0;
```

```
...
```

```
end STANDARD;
```

## APPENDIX F

### OF THE LANGUAGE REFERENCE MANUAL

The Ada language definition allows for certain target dependencies in a controlled manner. This section, called Appendix F as prescribed in the LRM, describes implementation-dependent characteristics of the Prime Primos Ada compilation system.

#### 1. Implementation-Defined Pragmas

pragma INTERFACE( Assembly, <subroutine\_name> );

pragma SUPPRESS( <condition\_name> [, on => <name> ] );

where: <condition\_name> is one of: access\_check, discriminant\_check, index\_check, length\_check, range\_check, division\_check, elaboration\_check, storage\_check.

pragma ELABORATE( <library\_unit\_name> {, <library\_unit\_name> } );

Specifies order of elaboration for the mentioned library units.

pragma PRIORITY ( <priority\_type> );

Specifies priority for a task.

Integer'First	-32_768
Integer'Last	32_767
Integer'Width	6
Long_Integer'First	-2_147_483_648
Long_Integer'Last	2_147_483_647
Long_Integer'Width	11
Float'Digits	6
Long_Float'Digits	9
Duration'Delta	.000060
Duration'First	-86_400.0
Duration'Last	86_400.0
Priority'First	0
Priority'Last	255
Any_Float'Machine_Rounds	False
Any_Real'Machine_Overflows	False
Any_Float'Machine_Radix	2
Any_Float'Machine_Emin	-127
Any_Float'Machine_Emax	127
Float'Mantissa	21
Long_Float'Mantissa	31

## 2. Package SYSTEM

The current specification of package SYSTEM is provided below.

PACKAGE System IS

```
PRAGMA Comment( "This is an unpublished work copyrighted by TeleSoft." );
PRAGMA Comment( "Copyright (c) 1983,1984 TeleSoft. All rights reserved." );
```

```
TYPE Address IS access Integer;
```

```
TYPE Subprogram_Value IS PRIVATE;
```

```
TYPE Name IS (Prime_Ada);
```

```
System_Name : CONSTANT name := Prime_Ada;
```

```
Storage_Unit : CONSTANT := 16;
```

```
Memory_Size : CONSTANT := (2 ** 8) * (2 ** 16);
```

```
-- System-Dependent Named Numbers:
```

```
Min_Int : CONSTANT := -(2**31);
```

```
Max_Int : CONSTANT := (2**31)-1;
```

```
Max_Digits : CONSTANT := 9;
```

```
Max_Mantissa : CONSTANT := 31;
```

```
Fine_Delta : CONSTANT := 1.0 / (2.0 ** (Max_Mantissa - 1));
```

```
Tick : CONSTANT := 1.0 / 330.0;
```

```
-- Other System-Dependent Declarations
```

```
SUBTYPE Priority IS Integer RANGE 0..255;
```

```
SUBTYPE Byte IS Integer RANGE 0..255;
```

```
Max_Object_Size : CONSTANT := 65536;
```

```
Max_Record_Count : CONSTANT := Max_Int;
```

```
Max_Text_Io_Count : CONSTANT := Max_Int-1;
```

```
Max_Text_Io_Field : CONSTANT := 1000;
```

PRIVATE

```
type ECB is record
```

```
  Start_Address : Address;
```

```
  Stack_Frame_Size : integer;
```

```
  Root_Seg_Num : integer;
```

```
  Arg_List_Dispatch : integer;
```

```
  Num_Args : integer;
```

```
  Link_Base : Address;
```

```
  Keys : integer;
```

end record;

type ECB\_Ptr is access ECB;

TYPE Subprogram\_Value IS record

  Task\_ECB : ECB\_Ptr;

  Parent\_SB : Address;

end record;

END System;

### **3. Representation Clauses**

Length clauses are supported for Size specification: T'SIZE and for the specification of small for a fixed point type: T'SMALL.

### **4. Implementation-Generated Names**

There are no implementation-generated names denoting implementation-dependent components. Names generated by the compiler shall not interfere with programmer-defined names.

### **5. Address Clause Expression Interpretation**

Expressions that appear in Address specifications are interpreted as the first storage unit of the object.

### **6. Unchecked Conversion Restrictions**

Unchecked conversions are allowed between types (or subtypes) T1 and T2 provided that:

- (1) They have the same static size.
- (2) They are not unconstrained array types.
- (3) They are not private (unless they are subtypes of or are derived from type SYSTEM.ADDRESS).
- (4) They are not types with discriminants.

### **7. Implementation-Dependent Characteristics of the I/O Packages**

- In Text\_IO, the type Count is defined as follows: type Count is range 0..2\_147\_483\_645;
- In Text\_IO, the type Field is defined as follows: subtype Field is integer range 0..1000;

### **8. Compilation of Generic Units**

The declaration, body, and any subunits of a generic unit must be submitted as a single compilation (i.e., must be in the same source file).

## 9. Restrictions on Machine Code Insertions

Machine code insertions are not supported in this release.

## 10. Definition of STANDARD

For this target system the numeric types and their properties are as follows:

### INTEGER

size = 16  
first = -32768  
last = +32767

### LONG\_INTEGER

size = 32  
first = -2\_147\_483\_648  
last = -2\_147\_483\_647

### FLOAT

size = 32  
machine\_rounds = FALSE  
machine\_overflows = FALSE  
machine\_radix = 2  
machine\_mantissa = 23  
machine\_emin = -127  
machine\_emax = +127  
first = -1.70141E+38  
last = 1.70141E+38

### LONG\_FLOAT

size = 48  
machine\_rounds = FALSE  
machine\_overflows = FALSE  
machine\_radix = 2  
machine\_mantissa = 56  
machine\_emin = -127  
machine\_emax = +127  
first = -1.70141183E+38  
last = 1.70141183E-38

### DURATION

size = 32  
delta = 2#1.0#e-14  
first = -86\_400.0  
last = +86\_400.0



APPENDIX C  
TEST PARAMETERS

Certain tests in the ACVC make use of implementation-dependent values, such as the maximum length of an input line and invalid file names. A test that makes use of such values is identified by the extension .TST in its file name. Actual values to be substituted are represented by names that begin with a dollar sign. A value must be substituted for each of these names before the test is run. The values used for this validation are given below.

<u>Name and Meaning</u>	<u>Value</u>
<u>\$BIG_ID1</u> Identifier the size of the maximum input line length with varying last character.	(1..199 =>'A', 200 =>'1')
<u>\$BIG_ID2</u> Identifier the size of the maximum input line length with varying last character.	(1..199 =>'A', 200 =>'2')
<u>\$BIG_ID3</u> Identifier the size of the maximum input line length with varying middle character.	(1..100   102..200 =>'A', 101 =>'3')
<u>\$BIG_ID4</u> Identifier the size of the maximum input line length with varying middle character.	(1..100   102..200 =>'A', 101 =>'4')
<u>\$BIG_INT_LIT</u> An integer literal of value 298 with enough leading zeroes so that it is the size of the maximum line length.	(1..197 =>'0', 198..200 =>"298")

# TEST PARAMETERS

Name and Meaning	Value
<p><b>\$BIG_REAL_LIT</b> A real literal that can be either of floating- or fixed-point type, has value 690.0, and has enough leading zeroes to be the size of the maximum line length.</p>	(1..194 =>'0', 195..200 =>"69.0E1")
<p><b>\$BLANKS</b> A sequence of blanks twenty characters fewer than the size of the maximum line length.</p>	(1..180 =>' ')
<p><b>\$COUNT_LAST</b> A universal integer literal whose value is TEXT_IO.COUNT'LAST.</p>	(2**31)-3
<p><b>\$EXTENDED_ASCII_CHARS</b> A string literal containing all the ASCII characters with printable graphics that are not in the basic 55 Ada character set.</p>	"abcdefghijklmnopqrstuvwxyz" & "!\$%?@[ ]^`{}~"
<p><b>\$FIELD_LAST</b> A universal integer literal whose value is TEXT_IO.FIELD'LAST.</p>	1000
<p><b>\$FILE_NAME_WITH_BAD_CHARS</b> An illegal external file name that either contains invalid characters, or is too long if no invalid characters exist.</p>	"X)}}!^#\$_Y"
<p><b>\$FILE_NAME_WITH_WILD_CARD_CHAR</b> An external file name that either contains a wild card character, or is too long if no wild card character exists.</p>	"XYZ@"
<p><b>\$GREATER_THAN_DURATION</b> A universal real value that lies between DURATION'BASE'LAST and DURATION'LAST if any, otherwise any value in the range of DURATION.</p>	86_401.0
<p><b>\$GREATER_THAN_DURATION_BASE_LAST</b> The universal real value that is greater than DURATION'BASE'LAST, if such a value exists.</p>	131_072.0

<u>Name and Meaning</u>	<u>Value</u>
\$ILLEGAL_EXTERNAL_FILE_NAME1 An illegal external file name.	"BAD-CHARACTER#^"
\$ILLEGAL_EXTERNAL_FILE_NAME2 An illegal external file name that is different from \$ILLEGAL_EXTERNAL_FILE_NAME1.	"MUCH_TOO_LONG_NAME_FOR_A_PRIMOS" & "_FILE_AND_THEN_SOME"
\$INTEGER_FIRST The universal integer literal expression whose value is INTEGER'FIRST.	-(2**31)
\$INTEGER_LAST The universal integer literal expression whose value is INTEGER'LAST.	(2**31)-1
\$LESS_THAN_DURATION A universal real value that lies between DURATION'BASE'FIRST and DURATION'FIRST if any, otherwise any value in the range of DURATION.	-86_401.0
\$LESS_THAN_DURATION_BASE_FIRST The universal real value that is less than DURATION'BASE'FIRST, if such a value exists.	-131_072.0
\$MAX_DIGITS The universal integer literal whose value is the maximum digits supported for floating-point types.	9
\$MAX_IN_LEN The universal integer literal whose value is the maximum input line length permitted by the implementation.	200
\$MAX_INT The universal integer literal whose value is SYSTEM.MAX_INT.	(2**31)-1

## TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
<p><b>\$NAME</b> A name of a predefined numeric type other than FLOAT, INTEGER, SHORT_FLOAT, SHORT_INTEGER, LONG_FLOAT, or LONG_INTEGER if one exists, otherwise any undefined name.</p>	LONG_INTEGER
<p><b>\$NEG_BASED_INT</b> A based integer literal whose highest order nonzero bit falls in the sign bit position of the representation for SYSTEM.MAX_INT.</p>	16#FFFFFFFE#
<p><b>\$NON_ASCII_CHAR_TYPE</b> An enumerated type definition for a character type whose literals are the identifier NON_NULL and all non-ASCII characters with printable graphics.</p>	(NON_NULL)

APPENDIX D  
WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. The following 19 tests had been withdrawn at the time of validation testing for the reasons indicated. A reference of the form "AI-ddddd" is to an Ada Commentary.

- . C32114A: An unterminated string literal occurs at line 62.
- . B33203C: The reserved word "IS" is misspelled at line 45.
- . C34018A: The call of function G at line 114 is ambiguous in the presence of implicit conversions.
- . C35904A: The elaboration of subtype declarations SFX3 and SFX4 may raise NUMERIC\_ERROR instead of CONSTRAINT\_ERROR as expected in the test.
- . B37401A: The object declarations at lines 126 through 135 follow subprogram bodies declared in the same declarative part.
- . C41404A: The values of 'LAST and 'LENGTH are incorrect in the if statements from line 74 to the end of the test.
- . B45116A: ARRPRIBL1 and ARRPRIBL2 are initialized with a value of the wrong type--PRIBOOL\_TYPE instead of ARRPRIBOOL\_TYPE--at line 41.
- . C48008A: The assumption that evaluation of default initial values occurs when an exception is raised by an allocator is incorrect according to AI-00397.
- . B49006A: Object declarations at lines 41 and 50 are terminated incorrectly with colons, and end case; is missing from line 42.
- . B4A010C: The object declaration in line 18 follows a subprogram body of the same declarative part.

## WITHDRAWN TESTS

- . B74101B: The begin at line 9 causes a declarative part to be treated as a sequence of statements.
- . C87B50A: The call of "/"= at line 31 requires a use clause for package A.
- . C92005A: The "/"= for type PACK.BIG\_INT at line 40 is not visible without a use clause for the package PACK.
- . C940ACA: The assumption that allocated task TT1 will run prior to the main program, and thus assign SPYNUMB the value checked for by the main program, is erroneous.
- . CA3005A..D (4 tests): No valid elaboration order exists for these tests.
- . BC3204C: The body of BC3204C0 is missing.

END  
DATE  
FILM  
4-88  
DTIC